



Dr. Jackets & Dr. Coats

**42" Dr. Jacket in GraLite®20 Back
Snap Strap SealTite® Sleeves**

072-4499-****

Dr. Jacket with a snap closure strap on the back and SealTite® sleeves

Any asterisk () shown in an Item No. will be replaced with a combination of digits identifying all of the options selected.*

This 42" long doctor style jacket is designed to provide full front and arm protection. It is also available as a 52" or 54" doctor style coat as well. The open back serves to ventilate the wearer and allows quick emergency removal. Adjustable straps snap or hook & loop close across the back of the neck, shoulders and waist to provide and individualized fit. Reinforcing bead is sewn around the collar for added durability. Dr. Coats and Dr. Jackets are manufactured to order. Video demonstrations on the installation and removal of the SealTite® Sleeve Insert and Gloves are available in the SUPPORT link on our website.

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.

42" Dr. Jacket in GraLite®20 Back Snap Strap SealTite® Sleeves

072-4499-****

Specs

Length-Dr:	42" (Dr. Jacket)
Fabric:	GraLite® 20
Closure-Dr:	Back Snap Strap
Units:	Each
Sleeves-Dr:	SealTite® Sleeve with Choice of Offered Gloves
Sizes:	All Sizes
Gloves:	Available options: <ul style="list-style-type: none">• Blue Kevlar®-Lined Triple Dipped PVC• Black Neoprene• Blue/Black Neoprene• Heavy Duty Black Neoprene• Red PVC• View Gloves & Sleeves category for specialty glove availability

Additional Garment Options:

Available options:

- Imprinted
 - Addition of 1 or 2 pockets available
 - +/- 3" increments to sleeve length
 - Addition of a hang-up loop
-



Contact Us:

Toll Free: (888) 345-4773

Phone: (815) 363-8565

info@standardsafety.com

www.standardsafety.com

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.