

**NO
PHOTO
AVAILABLE**

Half-C Maxi Vision Suits

Half-C Maxi Vision Suit in CPE

078-6785-XXXX

Half-C Maxi Vision

Any asterisk () shown in an Item No. will be replaced with a combination of digits identifying all of the options selected.*

The Half-C Maxi Vision is very similar to the Half-C Shoulder Mount Suit as it has a StaSafe® shoulder mount style hood attached to the body of a SealTite® sleeved garment having a 27" pressure-sealing zipper closure on the front closing from the shoulder to the bottom of the garment. The hood comes standard with a muffler installed in the crown for air circulation. While keeping the larger window and the muffler of the Half-C Shoulder Mount Suit, this suit hood portion is 3" taller to accommodate the headgear for a hard hat or ratchet headgear typically used with the Half-C Shell Suit. The cover window (20 mils thick) rests inside a snap-enclosed pocket for easy replacement and provides excellent range of vision while protecting the permanently sealed 40 mils thick inner window. A valve-belt and hose assembly provided with your choice of fittings completes the Half-C Maxi Vision Suit. Configure the suit to meet all your needs by choosing the glove options, optional 40 mil cover window or by customizing by adding options such as expanding the garment to accommodate a SCBA, installing a vent system, adding AC or elbow reinforcements to name a few. Video demonstrations on the installation and removal of the SealTite® Sleeve Insert and Gloves are available in the SUPPORT link on our website.

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.

Half-C Maxi Vision Suit in CPE

078-6785-XXXX

Specs

Fabric:

Units:

Sizes:

Fitting:

Available options:

- Brass Snap-Tite® Fitting
 - Hansen Fitting
 - Schrader Fitting
 - Snap-Tite® Fitting
 - Tru-Flate® Fitting
-

Gloves:

Available options:

- Blue Kevlar®-lined Triple Dipped PVC
 - Black Neoprene
 - Blue/Black Neoprene
 - Heavy Duty Black Neoprene
 - View Gloves & Sleeves category for specialty glove availability
-

Headgear-MV:

Available options:

- Maxi Ratchet Headgear
 - Maxi Ratchet Headgear & Extenders
 - Maxi Zip Clip
 - Maxi Zip Clip & Extenders
 - Maxi Zip Clip with Included Hard Cap with Ratchet Headgear
 - Maxi Zip Clip with Extenders and Included Hard Cap with Ratchet Headgear
-

Window-MV:

Cover Window Replacement-MV [ss]:

Available options:

- 077-1012-5424 - 20 mil Cover Window
 - 077-1012-5760 - 40 mil Cover Window
-

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.

Additional Options:**Available options:**

- Imprinted
- Addition of 1 or 2 pockets available
- +/- 3" increments to sleeve length available
- Retrieval D-Ring
- Additional Hangup Loops



Contact Us:

Toll Free: (888) 345-4773

Phone: (815) 363-8565

info@standardsafety.comwww.standardsafety.com

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.