Toll Free: (888) 345-4773
Phone: (815) 363-8565
info@standardsafety.com
www.standardsafety.com



Half-C Shell Suits

Half-C Shell Suit Back Zip in GraLite® 20

078-6569-****

Half-C Shell Suit Back Zip

Any asterisk (*) shown in an Item No. will be replaced with a combination of digits identifying all of the options selected.

The Half-C Shell Suit has a StaSafe® shell style hood attached to the body of a SealTite® sleeved garment having a 50” pressure-sealing zipper closure on the back. The hood section comes standard with adjustable ratchet headgear attached to a sturdy fiberglass reinforced frame. Other headgear options are available. The double window construction allows a 17” W X 8” H cover window (20 mils thick) to rest inside a snap-enclosed pocket for easy replacement and provides excellent range of vision while protecting the permanently sealed 40 mils thick inner window. A valve-belt and hose assembly -provided with choice of fittings completes the Half-C Shell Suit. Configure the suit to meet all your needs by choosing the glove material, headgear or add options such as expanding the garment to accommodate a SCBA or an egress bottle, or adding additional reinforcement at the elbow among other options. Video demonstrations on the installation and removal of the SealTite® Sleeve Insert and Gloves are available in the SUPPORT link on our website.

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.

Half-C Shell Suit Back Zip in GraLite® 20

078-6569-****

Specs

Entry-Shell Suits:	50" Pressure-sealing Zipper on Back of Garment
Fabric:	GraLite® 20
Units:	Each
Sizes:	All Sizes
Fitting:	**Available options:** • Brass Snap-Tite® Fitting • Hansen Fitting • Schrader Fitting • Snap-Tite® Fitting • Tru-Flate® Fitting
Gloves:	**Available options:** • Blue Kevlar®-Lined Triple Dipped PVC • Black Neoprene • Blue/Black Neoprene • Heavy Duty Black Neoprene • View Gloves & Sleeves category for specialty glove availability
Headgear-Shell Suits:	**Available options:** • Ratchet Headgear - Standard • Ratchet Headgear & Extenders • Installed Hard Cap with Ratchet Headgear
Window-Shell Suits:	40 mil Standard Window 20 mil Cover Window
Optional Cover Window-Shell Suits:	**Available options:** • 40 mil Cover Window • 42 mil Non-fog Cover Window

Contact Us:

Toll Free: (888) 345-4773
Phone: (815) 363-8565

info@standardsafety.com
www.standardsafety.com

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.