



### Half-C Shoulder Mount Suit

## Half-C Shoulder Mount Suit in HiGlo Expanded for Egress Bottle & SCBA

078-6877-\*\*\*\*

The garment is 6" longer than a typical Half-C and gradually flares from the chest to the hem of the garment to accommodate other apparatus the wearer may need under the hood. It has been expanded in the back to accommodate an SCBA.

*Any asterisk (\*) shown in an Item No. will be replaced with a combination of digits identifying all of the options selected.*

The Half-C Shoulder Mount Suit has a StaSafe® shoulder mount style hood attached to the body of a SealTite® sleeved garment having a 27" pressure-sealing zipper closure on the front closing from the shoulder to the bottom of the garment. The suit comes standard with a muffler installed in the crown for air circulation. The cover window (20 mils thick) rests inside a snap-enclosed pocket for easy replacement and provides excellent range of vision while protecting the permanently sealed 40 mils thick inner window. A valve-belt and hose assembly provided with your choice of fittings completes the Half-C Shoulder Mount Suit to provide chemical protection. Configure the suit to meet all your needs by choosing the glove options, optional 40 mil cover window or by customizing by adding options such as expanding the garment to accommodate a SCBA, installing a vent system, adding AC or elbow reinforcements to name a few. Half-C Shoulder Mount Suits are manufactured to order. Video demonstrations on the installation and removal of the SealTite® Sleeve Insert and Gloves are available in the SUPPORT link on our website.

### Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.

## Half-C Shoulder Mount Suit in HiGlo Expanded for Egress Bottle & SCBA

078-6877-\*\*\*\*

### Specs

Fabric:	HiGlo
Units:	Each
Sizes:	All Sizes
Gloves:	<b>Available options:</b> <ul style="list-style-type: none"><li>• Blue Kevlar®-Lined Triple Dipped PVC</li><li>• Black Neoprene</li><li>• Blue/Black Neoprene</li><li>• Heavy Duty Black Neoprene</li><li>• View Gloves &amp; Sleeves category for specialty glove availability</li></ul>
Window-SM Suits:	40 mil Standard Size Window 20 mil Cover Window
Optional Window-SM Suits:	<b>Available options:</b> <ul style="list-style-type: none"><li>• 40 mil Standard Size Window - 40 mil Cover Window</li></ul>
Cover Window Replacement-SM Suits [ss]:	<b>Available options:</b> <ul style="list-style-type: none"><li>• 077-1012-5424 - 20 mil Cover Window (standard sized)</li><li>• 077-1012-5760 - 40 mil Cover Window (standard size)</li></ul>
SCBA Back-SM Suits:	YES
Flared Bottom-SM Suits:	YES
Additional Garment Options:	<b>Available options:</b> <ul style="list-style-type: none"><li>• Imprinted</li><li>• Addition of 1 or 2 pockets available</li><li>• +/- 3" increments to sleeve length available</li><li>• Retrieval D-Ring</li><li>• Additional Hang-up Loops</li></ul>

### Contact Us:



Toll Free: (888) 345-4773

Phone: (815) 363-8565

[info@standardsafety.com](mailto:info@standardsafety.com)

[www.standardsafety.com](http://www.standardsafety.com)

### Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.