Toll Free: (888) 345-4773
Phone: (815) 363-8565
info@standardsafety.com
www.standardsafety.com



Jackets & Coats

30" Jacket in GraLite® Side Zipper Closure Standard Sleeves

072-3078-****

- 30"
- GraLite® fabric
- Side zipper closure
- Standard sleeves

Bib Overalls are sold separately.

Any asterisk (*) shown in an Item No. will be replaced with a combination of digits identifying all of the options selected.

Coats and Jackets can be manufactured in many configurations; your needs dictate the construction. The standard center snap closure is designed for ease of donning and doffing. An under flap provides a barrier of protection from splashes. The side closure design is constructed to protect from direct frontal splashes providing chemical protection. The one-piece body panel is fastened by an offset side zipper covered by a 1½" flap. A breakaway zipper offers quick removal of the jacket in emergencies. Select Jacket designs/sizes are stocked and may ship within 2 business days. The remaining jacket and coat designs and sizes are manufactured to order. Video demonstrations on the installation and removal of the SealTite® Sleeve Insert and Gloves are available in the SUPPORT link on our website.

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.

30" Jacket in GraLite® Side Zipper Closure Standard Sleeves

072-3078-****

Specs

Fabric:	GraLite®
Length:	30"
Units:	Each
Closure:	Side Zip
Sizes:	All Sizes
Hood Options:	No Parka Hood
Sleeves:	Standard Sleeve
Additional Options:	**Available options:** • Imprinted • Addition of 1 or 2 pockets available • +/- 3" increments to sleeve length available • Addition of a hang-up loop • Retrieval D-Ring

Contact Us:

Toll Free: (888) 345-4773
Phone: (815) 363-8565

info@standardsafety.com
www.standardsafety.com

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.