



#### NIOSH TC-19C-310 Hoods

### Shoulder-Mount Hood NIOSH approval TC-19C-310 Waist length in CPE

077-6555-\*\*\*\*

Waist length Shoulder Mount Hood in CPE with NIOSH approval

*Any asterisk (\*) shown in an Item No. will be replaced with a combination of digits identifying all of the options selected.*

A specific line of StaSafe® Shoulder Mount Hoods has a NIOSH Approval as a Continuous-Type C Flow Class respirator. The NIOSH approval allows the wearer to enter areas that are not immediately dangerous to life or health without the need of a cumbersome tight-fitting respirator. This waist-length reusable chemical resistant hood offers combination chemical and Type C Respiratory protection. The hood comes with a 19" X 12" replaceable cover window and is lightweight and roomy. NIOSH Shoulder Mount Hoods are manufactured to order.

#### Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.

## Shoulder-Mount Hood NIOSH approval TC-19C-310 Waist length in CPE

077-6555-\*\*\*\*

### Specs

---

Fabric:	CPE
Units:	Each
Fitting:	<b>Available options:</b> <ul style="list-style-type: none"><li>• Hansen Fitting</li><li>• Schrader Fitting</li><li>• Snap-Tite® Fitting</li><li>• Brass Snap-Tite® Fitting</li><li>• Tru-Flate® Fitting</li></ul>

---

Cover Window Replacement [ss]:	<b>Available options:</b> <ul style="list-style-type: none"><li>• 077-1012-5424 - 20 mil Cover Window (standard sized)</li><li>• 077-1012-5760 - 40 mil Cover Window (standard size)</li></ul>
--------------------------------	--

---



### Contact Us:

Toll Free: (888) 345-4773

Phone: (815) 363-8565

[info@standardsafety.com](mailto:info@standardsafety.com)

[www.standardsafety.com](http://www.standardsafety.com)

---

### Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.