

PVC Gloves

Blue Triple-Dipped PVC Gloves

079-6660-****

Triple-dipped PVC-coated glove with a rough textured layer covering the hand area providing a good grip and feel. The seamless white cotton liner absorbs perspiration. A vinyl bead of welting is sewn into the gauntlet portion of the glove. This beading retains the plastic insert that is required to effect the SealTite® Sleeve joint.



The 079-6661 Blue Triple-dipped Kevlar®-lined glove is sold with StaSafe PVC garments. Please note the difference in permeation breakthrough times.

IMPORTANT NOTE REGARDING LIABILITY: Standard Safety Equipment Company will not assume liability if our factory beaded gloves are not used in conjunction with our SealTite® Sleeve system.

Chemical Breakthrough Times in Minutes

Hydrofluoric Acid 48-50%	>156
Hydrogen Fluoride 99%	>13

Available in cases of 24 pairs.

Any asterisk () shown in an Item No. will be replaced with a combination of digits identifying all of the options selected.*

Gloves are fully coated with polyvinyl chloride (PVC) on top of an interlock liner. A vinyl bead of welting is sewn into the gauntlet portion of the glove. This beading retains the plastic insert that is required to effect the SealTite® Sleeve joint. **IMPORTANT NOTE REGARDING LIABILITY:** Standard Safety Equipment Company will not assume liability if our factory beaded gloves are not used in conjunction with our SealTite® Sleeve system.

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.

Blue Triple-Dipped PVC Gloves

079-6660-****



Blue Triple-Dipped PVC Gloves 079-6660-2402
Size Medium



Blue Triple-Dipped PVC Gloves 079-6660-2403
Size Large



Blue Triple-Dipped PVC Gloves 079-6660-2404
Size X Large



Blue Triple-Dipped PVC Gloves 079-6660-2405
Size 2X Large



Contact Us:

Toll Free: (888) 345-4773

Phone: (815) 363-8565

info@standardsafety.com

www.standardsafety.com

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.