



#### Steel-Toe

### Green Hazmax Steel Toe Boots

168-8701-\*\*\*\*

16" Green boot with a steel toe that complies with ASTM F2413-05 and CSA Z195 and a steel shank and midsole. The one-piece PVC construction makes this a suitable boot for use in environments involving chemicals.

*Any asterisk (\*) shown in an Item No. will be replaced with a combination of digits identifying all of the options selected.*

Many industrial situations require the use of a steel-toe boot. In addition to making steel-toe boots available, we also offer the option of permanently attaching the boot to the leg cuff of our garments.

---

#### Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.

## Green Hazmax Steel Toe Boots

168-8701-\*\*\*\*



16" Green Hazmax Steel Toe Boots 168-8701-1007  
Size 7



16" Green Hazmax Steel Toe Boots 168-8701-1008  
Size 8



16" Green Hazmax Steel Toe Boots 168-8701-1009  
Size 9



16" Green Hazmax Steel Toe Boots 168-8701-1010  
Size 10



16" Green Hazmax Steel Toe Boots 168-8701-1011  
Size 11



16" Green Hazmax Steel Toe Boots 168-8701-1012  
Size 12



16" Green Hazmax Steel Toe Boots 168-8701-1013  
Size 13



16" Green Hazmax Steel Toe Boots 168-8701-1014  
Size 14



16" Green Hazmax Steel Toe Boots 168-8701-1015  
Size 15

### Contact Us:



Toll Free: (888) 345-4773

Phone: (815) 363-8565

[info@standardsafety.com](mailto:info@standardsafety.com)

[www.standardsafety.com](http://www.standardsafety.com)

## Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.