



Switch Puller Jackets

Switch Puller Jacket in GraLite® 20 Standard Sleeves

072-6253-****

One-piece, 43" long solid front so it must be pulled on over the head and has standard sleeves. A gusset with a concealed hook and loop closure has been added to the front neckline to give an extra-large opening. The opening below the waist provides complete freedom of movement and ventilation. No metal is used in the garment.

Any asterisk () shown in an Item No. will be replaced with a combination of digits identifying all of the options selected.*

The Switch Pullers Jacket manufactured from GraLite® 20 has been designed to provide protection from arcing at manual or automatic switching gear. The garment has a one-piece, 43" long solid front so it must be pulled on over the head and has standard sleeves. A gusset with a concealed hook and loop closure has been added to the front neckline to give an extra-large opening. The back extending from the shoulders to the waist has been pleated in two places for ease of donning and doffing. The opening below the waist provides complete freedom of movement and ventilation. No metal is used in the garment. This jacket eliminates the need for a heavy, bulky coat that is uncomfortable for the worker to wear. Switch Puller Jackets are manufactured to order.

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.

Switch Puller Jacket in GraLite® 20 Standard Sleeves

072-6253-****

Specs

Fabric:	GraLite® 20
Units:	Each
Sizes:	All Sizes
Length:	Available options: <ul style="list-style-type: none">• 43"

Additional Garment Options:	Available options: <ul style="list-style-type: none">• Imprinted• Addition of 1 or 2 pockets• +/- 3" increments to sleeve length• Addition of a hang-up loop
-----------------------------	---



Contact Us:

Toll Free: (888) 345-4773

Phone: (815) 363-8565

info@standardsafety.com

www.standardsafety.com

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.