



Training TEG

TEG Training Suit in HiGlo

076-7028-000*

TEG Training Suit is manufactured for training purposes only and does not provide protection from hazardous chemicals to the wearer. It has sewn-only seams that are not sealed against chemical penetration. This suit omits the SealTite® cuff system and has permanently attached blue Kevlar®-lined triple-dipped PVC gloves and HiGlo stocking foot booties sewn to the bottom of the leg.

Any asterisk () shown in an Item No. will be replaced with a combination of digits identifying all of the options selected.*

Choose the TEG Training Suit for an economical way to train your workers the proper donning and doffing techniques of the TEG. This suit is manufactured from HiGlo fabric and has sewn-only seams. Blue Kevlar®-lined triple-dipped PVC gloves have been permanently attached to the sleeves and the stocking foot booties are made from HiGlo and are sewn to the legs. These suits are easily identified not only by the color of the fabric but also by the "TRAINING SUIT" imprint on the chest and center back. These suits are not to be worn in hazardous conditions as they do not provide the necessary chemical protection. TEG Training suits are manufactured to order.

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.

TEG Training Suit in HiGlo

076-7028-000*

Specs

TEG Type:	Training Suit
Fabric:	HiGlo
Attached Footwear:	Attached Stocking Foot Booties - HiGlo
Units:	Each
Sizes:	All Sizes
Seams:	Sewn-Only seams
Sleeve:	Attached Glove Sleeve with Blue Kevlar®-Lined Triple-Dipped PVC Gloves

Contact Us:



Toll Free: (888) 345-4773

Phone: (815) 363-8565

info@standardsafety.com

www.standardsafety.com

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.