Toll Free: (888) 345-4773
Phone: (815) 363-8565
info@standardsafety.com
www.standardsafety.com

WorkMaster®

Front Entry WorkMaster® in CPE Attached Stocking Foot Booties Vent AC hardware

076-7064-****



- CPE Front entry WorkMaster®
- Attached stocking foot booties
- Choice of offered gloves
- Option to add offered boots
- 40 mil cover window
- INCLUDES Vent system with choice of offered fittings
- Fabric hold-down channels in arms and legs
- Reinforced area for AC unit
- AC connecting hardware with an adjustable air valve inside the suit for customer's AC unit

An air pass-through, sold separately, is required, and must be added at time of order.

Any asterisk (*) shown in an Item No. will be replaced with a combination of digits identifying all of the options selected.

The StaSafe® WorkMaster®, available with front or rear zipper entry, is a Level A protective suit with a streamlined design. It provides ample room in the shoulders, allowing the wearer to easily remove their arms from the sleeves. The WorkMaster® eliminates the need for a 30 or 60 minute SCBA; it causes less fatigue during long hours of use. Available with numerous pass-throughs options. All WorkMaster® suits come with an All-Purpose Hood, which offers an extra large window providing unhampered head movement and include a 40 mil cover window. WorkMaster® suits come with SealTite® glove assembly. This assembly provides a liquid-tight, vapor-tight seal when worn with one of our beaded gloves that offers optimum protection. A rigid plastic insert is fitted inside the glove gauntlet and tapered sleeve cuff. The side pouch is standard on all WorkMaster® garments and accommodates numerous egress bottles. Various boot configurations are available on the WorkMaster®. Other options include, vent system, AC, or reinforcing patches at the knee, elbow or crotch. Every WorkMaster® must comply with the ASTM1052 inflation testing standard to ensure its air-tight integrity before leaving the factory. WorkMaster® suits are manufactured to order. Video demonstrations on the installation and removal of the SealTite® Sleeve Insert and Gloves are available in the SUPPORT link on our website.

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.

Front Entry WorkMaster® in CPE Attached Stocking Foot Booties Vent AC hardware

076-7064-****

Specs

Entry-WorkMaster:	Front Entry
Fabric:	CPE
Units:	Each
Sizes:	All Sizes
Gloves for CPE Fabric:	**Available options:** • Black Neoprene • Heavy Duty Black Neoprene • View Gloves & Sleeves category for specialty glove availability
Attached Footwear-WorkMaster:	Attached CPE Stocking Foot Booties
Boots Available with Stocking Foot Booties-WorkMaster:	**Available options:** • Hazmax® Steel-toe Boots • PVC Composite-safety-toe Boots
Cover Window-WorkMaster:	YES
Cover Window Replacement-WorkMaster [ss]:	**Available options:** • 807-8006-0050 - 40 mil Cover Window
AC-Vent-WorkMaster:	Vent
Fitting for Vent:	**Available options:** • Brass Snap-Tite® Fitting • Hansen Fitting • Schrader Fitting • Snap-Tite® Fitting • Tru-Flate® Fitting
Pass-through Available [ss]:	YES
Customer-supplied Pass-through Installation Available:	YES

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.

Additional Garment Options:	**Available options:** • Imprinted • Addition of 1 or 2 pockets available • +/- 3" increments to sleeve length available • Addition of hang-up loops
Retrieval D-Ring Available [ss]:	YES

Contact Us:

Toll Free: (888) 345-4773
Phone: (815) 363-8565

info@standardsafety.com
www.standardsafety.com

Limitation of Liability

This information is based upon technical data that Standard Safety Equipment Company believes to be reliable. It is subject to revision as additional knowledge and experience are gained. Standard Safety Equipment Company makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded, or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including without limitations, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of Standard Safety Equipment Company or others covering any material or its use.